# **SAFETY DATA SHEET**

GHS United States

# Section 1. Product and company identification

A Wholly Owned Subsidiary of R.T. Vanderbilt Holding Company, Inc.

Product name	VANLINK® 7-70	In case of emergency
Code	50374	1-203-853-1400 Chemtrec: 1-800-424-9300
Supplier/Manufacturer	Vanderbilt Chemicals, LLC 30 Winfield Street Norwalk, CT 06855	Outside US: +1-703-527-3887
Synonym	Not available.	
Material uses	Co-Agent	

Product type Powder.

# Section 2. Hazards identification

OSHA/HCS status	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the	COMBUSTIBLE DUSTS
substance or mixture	ACUTE TOXICITY (oral) - Category 4 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
GHS label elements	
Hazard pictograms	
Signal word	Warning
Hazard statements	Harmful if swallowed. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. (liver) (oral) May form combustible dust concentrations in air.
Precautionary statements	
Prevention	Obtain special instructions before use. Wear protective gloves. Wear protective clothing: Recommended: lab coat. Wear eye or face protection: Recommended: safety glasses with side-shields Do not breathe dust or mist. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.
Response	IF exposed or concerned: Get medical advice or attention.
Storage	Not applicable.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Prevent dust accumulation.
Hazards not otherwise classified	None known.

Validation date	11	10/24/2022	
vanuation uate		10/24/2022	

### Section 2. Hazards identification

# Section 3. Composition/information on ingredients

### Substance/mixture

Mixture

Ingredient name	CAS number	% by weight
triallyl isocyanurate	1025-15-6	67 - 73
silica	7631-86-9	27 - 33

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

### **Description of necessary first aid measures**

Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

Potential acute health ef	f <u>fects</u>
Eye contact	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	No known significant effects or critical hazards.
Ingestion	Harmful if swallowed.
Over-exposure signs/sy	<u>mptoms</u>
Eye contact	Adverse symptoms may include the following: irritation redness

# Section 4. First aid measures

Inhalation	Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	No specific data.
Ingestion	No specific data.
Indication of immediate med	ical attention and special treatment needed, if necessary
Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	In case of fire, use water spray (fog), foam, dry chemical or $CO_2$ .
Unsuitable extinguishing media	Do not use water jet.
Specific hazards arising from the chemical	May form explosible dust-air mixture if dispersed.
Hazardous thermal decomposition products	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

Personal precautions, protecti	ve equipment and emergency procedures
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

# Section 6. Accidental release measures

Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for cont	ainment and cleaning up
Small spill	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

Precautions for safe handling	
Protective measures	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe dust. Do not ingest. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

### **Control parameters**

### **Occupational exposure limits**

Ingredient name	Exposure limits
silica	OSHA PEL TWA: 50 μg/m3 excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays 50 μg/m3 TWA 25 μg/m3 Action Level TWA: 20 mppcf: (80)/(% SiO2) mg/m3 TWA (vacated) TWA: 6 mg/m3 <1% Crystalline silica

Appropriate engineering controls	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side- shields. If operating conditions cause high dust concentrations to be produced, use dust goggles. Recommended: safety glasses with side-shields.
Skin protection	
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: lab coat
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 8. Exposure controls/personal protection

Personal protective equipment (Pictograms)



# Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	Solid. [Powder.]
Color	White.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point	26 to 28°C (78.8 to 82.4°F)
Boiling point	Not available.
Flash point	Not available.
Burning time	Not available.
Burning rate	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Lower and upper explosive (flammable) limits	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Density	Not available.
Relative density	Not available.
Solubility	Not available.
Solubility in water	Not available.
Partition coefficient: n- octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
SADT	Not available.
Viscosity	Not available.

# Section 10. Stability and reactivity

Reactivity	No specific test data related to reactivity available for this product or its ingredients.		
Chemical stability	The product is stable.		
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.		
Conditions to avoid	Heat, flames, sparks, ignition sources and contamination.		
Validation date : 10/24/2022	Date of previous issue : 8/17/2020	6/12	

### Section 10. Stability and reactivity

# Incompatible materialsReactive or incompatible with the following materials:<br/>acids<br/>oxidizing agentsHazardous decompositionUnder normal conditions of storage and use bazardo

Hazardous decomposition<br/>productsUnder normal conditions of storage and use, hazardous decomposition products should<br/>not be produced.

# Section 11. Toxicological information

### Information on toxicological effects

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
triallyl isocyanurate	LD50 Dermal LD50 Oral	Rat Rat	2750 mg/kg 707 mg/kg	-
silica	LC50 Inhalation Dusts and mists LD50 Dermal	Rat Rabbit	>2.2 mg/l >2000 mg/kg	4 hours -
	LD50 Oral	Rat	>5000 mg/kg	-

### Irritation/Corrosion

Not available.

Conclusion/Summary	
Skin	Triallyl isocyanurate: Non-irritating to the skin. (Rabbit)
Eyes	Triallyl isocyanurate: Non-irritating to the eyes. (Rabbit)

#### **Sensitization**

• • • • • • • • • • • • • • • • • • • •	Route of exposure	Species	Result
triallyl isocyanurate	skin	Guinea pig	Not sensitizing

### **Mutagenicity**

Product/ingredient name	Test	Experiment	Result
triallyl isocyanurate	OECD 471	Experiment: In vitro Subject: Bacteria	Negative
	OECD 474	Experiment: In vivo Subject: Mammalian-Animal	Negative

### Carcinogenicity

Not available.

Product/ingredient name	OSHA	IARC	NTP
silica	-	3	-

### Reproductive toxicity

Not available.

# Section 11. Toxicological information

### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
triallyl isocyanurate	Category 2	oral	liver

### Aspiration hazard

Not available.

nformation on the likely routes of exposure	Routes of entry anticipated: Inhalation.
Potential acute health effects	
Eye contact	Exposure to airborne concentrations above statutory or recommended exposur limits may cause irritation of the eyes.
Inhalation	Exposure to airborne concentrations above statutory or recommended exposur limits may cause irritation of the nose, throat and lungs.
Skin contact	May be harmful in contact with skin.
Ingestion	Harmful if swallowed.
Symptoms related to the phys	ical, chemical and toxicological characteristics
Eye contact	Adverse symptoms may include the following: irritation redness
Inhalation	Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	No specific data.
Ingestion	No specific data.
Delayed and immediate effect	s and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	Not available.
Potential delayed effects	Not available.
Long term exposure	
Potential immediate effects	Not available.
Potential delayed effects	Not available.
Potential chronic health effe	<u>cts</u>

# Section 11. Toxicological information

General	May cause damage to organs through prolonged or repeated exposure if swallowed. Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.
Carcinogenicity	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
<b>Developmental effects</b>	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

### **Numerical measures of toxicity**

### Acute toxicity estimates

Route	ATE value
	500 mg/kg 2669.9 mg/kg

### **Other information**

Not available.

# Section 12. Ecological information

Toxicity			
Product/ingredient name	Result	Species	Exposure
triallyl isocyanurate	Acute EC50 >100 mg/l	Algae	72 hours
	Acute EC50 340 mg/l	Daphnia	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
silica	Acute EC50 440 mg/l	Algae	72 hours
	Acute LC50 5000 mg/l	Fish	96 hours

### Persistence and degradability

Product/ingredient name	Test	Result		Dose		Inoculum
triallyl isocyanurate	OECD 301C	7 % - Not re	eadily - 28 days	-		-
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
triallyl isocyanurate	-		-		Not rea	ıdily

### Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
triallyl isocyanurate	2.2	-	low

### Mobility in soil

Soil/water partition coefficient (Koc)

Not available.

#### Other adverse effects

No known significant effects or critical hazards.

### Section 13. Disposal considerations

### **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

### Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	Not regulated.	-	-	-		-
TDG Classification	Not regulated.	-	-	-		-
ADR/RID Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-
IATA-DGR Class	Not regulated.	-	-	-		-

PG\* : Packing group

# Section 15. Regulatory information

United States Inventory (TSCA 8b)

All components are active or exempted.

**U.S. Federal regulations** 

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

### SARA 302/304

**Composition/information on ingredients** 

No products were found.

 SARA 304 RQ
 Not applicable.

 SARA 311/312
 COMBUSTIBLE DUSTS

 Classification
 COMBUSTIBLE DUSTS

 ACUTE TOXICITY (oral) - Category 4

 CARCINOGENICITY - Category 2

 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

**Composition/information on ingredients** 

# Section 15. Regulatory information

Name	%	Classification
triallyl isocyanurate		ACUTE TOXICITY (oral) - Category 4 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
silica	47 - 53	CARCINOGÉNICITY - Category 2

### State regulations

Massachusetts	The following components are listed: DIATOMACEOUS EARTH; AMORPHOUS SILICA
New York	None of the components are listed.
New Jersey	None of the components are listed.
Pennsylvania	The following components are listed: SILICA
California Prop. 65	<b>WARNING</b> : This product can expose you to silica, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingr			Maximum acceptable dosage level
silic	a	-	-

International regulations	
Australia Inventory (AIIC)	All components are listed or exempted.
Canada Inventory	All components are listed or exempted.
China Inventory (IECSC)	All components are listed or exempted.
Europe inventory	All components are listed or exempted.
Japan Inventory (CSCL)	All components are listed or exempted.
Korea inventory (KECI)	All components are listed or exempted.
New Zealand Inventory of Chemicals (NZIoC)	All components are listed or exempted.
Philippines Inventory (PICCS)	All components are listed or exempted.
Taiwan Chemical Substances Inventory (TCSI)	All components are listed or exempted.

### Section 16. Other information

Hazardous Material Identification System (U.S.A.)

Health	2
Flammability	0
Physical hazards	0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

### Section 16. Other information

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

#### National Fire Protection Association (U.S.A.)



Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

#### **History**

Date of printing Validation date Date of previous issue	10/24/2022 10/24/2022 8/17/2020
Version	2
Key to abbreviations	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
References	Not available.
Information contact	Vanderbilt Global Services, LLC Corporate Risk Management
	1-203-295-2143

#### Visit www.vanderbiltchemicals.com for more information.

#### Notice to reader

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material supplied by us.