

SAFETY DATA SHEET

 GHS
 United States

Section 1. Product and company identification

| | | |
|------------------------------|--|--|
| Product name | VANLUBE® 1202 | <u>In case of emergency</u> |
| Code | 53473 | 1-203-853-1400 |
| Supplier/Manufacturer | Vanderbilt Chemicals, LLC 30 Winfield Street Norwalk, CT 06855 | Chemtrec: 1-800-424-9300 Outside US: +1-703-527-3887 |
| Synonym | Not available. | |
| Material uses | Lubricant additives | |
| Product type | Powder. | |

Section 2. Hazards identification

OSHA/HCS status This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture COMBUSTIBLE DUSTS

GHS label elements

Signal word Warning

Hazard statements May form combustible dust concentrations in air.

Precautionary statements

Prevention Not applicable.

Response Not applicable.

Storage Not applicable.

Disposal Not applicable.

Supplemental label elements Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Prevent dust accumulation.

Hazards not otherwise classified None known.

Section 3. Composition/information on ingredients

Substance/mixture Substance

| Ingredient name | CAS number | % by weight |
|-----------------|------------|-------------|
| Alkylated PANA | - | 100 |

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

| | |
|---------------------|---|
| Eye contact | Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs. |
| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Skin contact | Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse. |
| Ingestion | Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |

Most important symptoms/effects, acute and delayed

Potential acute health effects

| | |
|---------------------|--|
| Eye contact | Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes. |
| Inhalation | Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs. |
| Skin contact | No known significant effects or critical hazards. |
| Ingestion | No known significant effects or critical hazards. |

Over-exposure signs/symptoms

| | |
|---------------------|---|
| Eye contact | Adverse symptoms may include the following: irritation redness |
| Inhalation | Adverse symptoms may include the following: respiratory tract irritation coughing |
| Skin contact | No specific data. |
| Ingestion | No specific data. |

Indication of immediate medical attention and special treatment needed, if necessary

| | |
|-----------------------------------|--|
| Notes to physician | In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Specific treatments | No specific treatment. |
| Protection of first-aiders | No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |

See toxicological information (Section 11)

Section 4. First aid measures

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

In case of fire, use water spray (fog), foam, dry chemical or CO₂.

Unsuitable extinguishing media

Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.

Specific hazards arising from the chemical

May form explosible dust-air mixture if dispersed.

Hazardous thermal decomposition products

Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Remark

Decomposition may occur at temperatures greater than 350°C.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

Appropriate engineering controls

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 8. Exposure controls/personal protection

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. If operating conditions cause high dust concentrations to be produced, use dust goggles. Recommended: safety glasses with side-shields

Skin protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: lab coat


Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Vapor and dust respirator.

Personal protective equipment (Pictograms)



Section 9. Physical and chemical properties

Appearance

| | |
|--|---|
| Physical state | Solid. [Powder.] |
| Color | Yellowish-brown. |
| Odor | Odorless. |
| Odor threshold | Not available. |
| pH | 6.5 [Conc. (% w/w): 1%, as suspension] |
| Melting point | >75°C (>167°F) |
| Boiling point | Not available. |
| Flash point | Closed cup: 186°C (366.8°F) [Pensky-Martens.] |
| Burning time | Not available. |
| Burning rate | Not available. |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Decomposition may occur at temperatures greater than 350°C. |
| Lower and upper explosive (flammable) limits | Not available. |
| Vapor pressure | 0.000007 Pa [25°C] |
| Vapor density | Not available. |
| Density | Not available. |
| Relative density | Not available. |

Section 9. Physical and chemical properties

| | |
|---|----------------|
| Solubility | Not available. |
| Solubility in water | Not available. |
| Partition coefficient: n-octanol/water | Not available. |
| Auto-ignition temperature | 440°C (824°F) |
| Decomposition temperature | Not available. |
| SADT | Not available. |
| Viscosity | Not available. |

Section 10. Stability and reactivity

| | |
|---|---|
| Reactivity | No specific test data related to reactivity available for this product or its ingredients. |
| Chemical stability | The product is stable. |
| Possibility of hazardous reactions | Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation. |
| Incompatible materials | Reactive or incompatible with the following materials: oxidizing materials |
| Hazardous decomposition products | Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|-----------------------|---------|-------------|----------|
| Alkylated PANA | LC50 Inhalation Vapor | Rat | >0.4 mg/l | 4 hours |
| | LD50 Dermal | Rat | >2000 mg/kg | - |
| | LD50 Oral | Rat | >2000 mg/kg | - |

Irritation/Corrosion

Not available.

Conclusion/Summary

| | |
|-------------|---|
| Skin | Alkylated PANA: Non-irritating to the skin. (Reconstructed Human Epidermis Test Method) |
| Eyes | Alkylated PANA: Non-irritating to the eyes. (EpiOcular human cell construct) |

Sensitization

Section 11. Toxicological information

| Product/ingredient name | Route of exposure | Species | Result |
|-------------------------|-------------------|------------|-----------------|
| Alkylated PANA | skin | Guinea pig | Not sensitizing |

Mutagenicity

| Product/ingredient name | Test | Experiment | Result |
|-------------------------|----------|---|----------|
| Alkylated PANA | OECD 471 | Experiment: In vitro Subject: Bacteria | Negative |
| | OECD 476 | Experiment: In vitro Subject: Mammalian-Animal | Negative |
| | OECD 471 | Experiment: In vitro Subject: Mammalian-Animal | Negative |

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Conclusion/Summary

Alkylated PANA: Based on these results, a parental, reproduction and developmental No Observed Adverse Effect Level (NOAEL) of at least 1000 mg/kg bw/day was derived.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Eye contact

Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.

Inhalation

Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.

Skin contact

May be harmful in contact with skin.

Ingestion

May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Section 11. Toxicological information

| | |
|---------------------|---|
| Eye contact | Adverse symptoms may include the following: irritation redness |
| Inhalation | Adverse symptoms may include the following: respiratory tract irritation coughing |
| Skin contact | No specific data. |
| Ingestion | No specific data. |

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects Not available.

Potential delayed effects Not available.

Long term exposure

Potential immediate effects Not available.

Potential delayed effects Not available.

Potential chronic health effects

Not available.

Conclusion/Summary Alkylated PANA: Based on the results presented, a No Observed Adverse Effect Level (NOAEL) of at least 1000 mg/kg bw/day was derived.

General Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

Carcinogenicity No known significant effects or critical hazards.

Mutagenicity No known significant effects or critical hazards.

Teratogenicity No known significant effects or critical hazards.

Developmental effects No known significant effects or critical hazards.

Fertility effects No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

| Route | ATE value |
|--------------|------------------|
| Oral | 2500 mg/kg |
| Dermal | 2500 mg/kg |

Other information Not available.

Section 12. Ecological information

Toxicity

Section 12. Ecological information

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|---|----------------|----------|
| Alkylated PANA | Acute EC50 >100 mg/l No effect up to the limit of solubility. | Algae | 72 hours |
| | Acute EC50 >100 mg/l No effect up to the limit of solubility. | Daphnia | 48 hours |
| | Acute IC50 >100 mg/l No effect up to the limit of solubility. | Micro-organism | 3 hours |
| | Acute LC50 >100 mg/l No effect up to the limit of solubility. | Fish | 96 hours |

Persistence and degradability

| Product/ingredient name | Test | Result | Dose | Inoculum |
|-------------------------|-----------|-----------------------------|------|----------|
| Alkylated PANA | OECD 301B | 0 % - Not readily - 28 days | - | - |

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| Alkylated PANA | - | - | Not readily |

Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|-------------------------|--------------------|-----|-----------|
| Alkylated PANA | - | 17 | low |

Mobility in soil

Soil/water partition coefficient (K_{oc}) Not available.

Other adverse effects No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Section 14. Transport information

| Regulatory information | UN number | Proper shipping name | Classes | PG* | Label | Additional information |
|---------------------------|----------------|----------------------|---------|-----|-------|------------------------|
| DOT Classification | Not regulated. | - | - | - | | - |
| TDG Classification | Not regulated. | - | - | - | | - |
| ADR/RID Class | Not regulated. | - | - | - | | - |
| IMDG Class | Not regulated. | - | - | - | | - |
| IATA-DGR Class | Not regulated. | - | - | - | | - |

PG* : Packing group

Section 15. Regulatory information

[United States inventory \(TSCA 8b\)](#) All components are listed or exempted.

[U.S. Federal regulations](#)

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

[SARA 302/304](#)

[Composition/information on ingredients](#)

No products were found.

[SARA 304 RQ](#)

Not applicable.

[SARA 311/312](#)

[Classification](#)

COMBUSTIBLE DUSTS

[Composition/information on ingredients](#)

No products were found.

[State regulations](#)

[Massachusetts](#)

None of the components are listed.

[New York](#)

None of the components are listed.

[New Jersey](#)

None of the components are listed.

[Pennsylvania](#)

None of the components are listed.

[California Prop. 65](#)

None of the components are listed.

[International regulations](#)

[Australia inventory \(AICS\)](#)

All components are listed or exempted.

[Canada inventory](#)

All components are listed or exempted.

[China inventory \(IECSC\)](#)

All components are listed or exempted.

[Europe inventory](#)

All components are listed or exempted.

[Japan inventory \(ENCS\)](#)

All components are listed or exempted.

[Korea inventory \(KECI\)](#)

All components are listed or exempted.

Section 15. Regulatory information

| | |
|---|--|
| New Zealand Inventory of Chemicals (NZIoC) | All components are listed or exempted. |
| Philippines inventory (PICCS) | All components are listed or exempted. |
| Taiwan Chemical Substances Inventory (TCSI) | All components are listed or exempted. |

Section 16. Other information

[Hazardous Material Identification System \(U.S.A.\)](#)

| | |
|------------------|---|
| Health | 0 |
| Flammability | 1 |
| Physical hazards | 0 |
| | |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

[National Fire Protection Association \(U.S.A.\)](#)



Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

[History](#)

| | |
|--|---|
| Date of printing | 3/20/2019 |
| Validation date | 3/20/2019 |
| Date of previous issue | 10/11/2018 |
| Version | 4 |
| Key to abbreviations | <p>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations</p> |

Section 16. Other information

| | |
|----------------------------|---|
| References | Not available. |
| Information contact | Vanderbilt Global Services, LLC Corporate Risk Management 1-203-295-2143 |

Visit www.vanderbiltchemicals.com for more information.

Notice to reader

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material supplied by us.