



Denka Chloroprene Technical Data Sheet

LM-61

DENKA CHLOROPRENE LATEX LM-61 is a low viscosity and high solid anionic chloroprene latex.

Typical Product Properties*	
CAS No.	9010-98-4
Polymer Type	Anionic
Crystallization Rate	Medium
Gel Content	High
Solids, % by weight	60 ± 1
pH at 25°C[77°F]	≥12
Viscosity[mPa · s]	60-200
* These data are presented to describe LM-61 and are not intended to serve as specifications.	

Application

Adhesives, dipping products. Coatings

Denka Company Limited

Elastomer Department, Elastomers & Infrastructure Solutions

Head Office Nihonbashi Mitsui Tower,1-1,Nihonbashi-Muromachi 2-chome,Chuo-ku,Tokyo 103-8338,JAPAN

Telephone: +81-3-5290-5550

FAX: +81-3-5290-5400

email: 010261@denka.co.jp

The information set forth in this technical data sheet is presented based on typical experiments and investigations and we make no warranty, expressed or implied, concerning our products.

It is the responsibility of each user to ensure that our products are suitable and safe for the application by testing before use.

Please comply with national or local laws and legislations related to our products or any other products containing our products in its disposal.

Before using our products, please see their SDS (Safety Data Sheet) for detailed information. Please contact us if you require such information or any other assistance from us regarding our products. Especially when using our products in specialized fields such as medical application, please consult us before use.

