

Specification

PYRAX[®] B **Pyrophyllite**

January 27, 2017

RTV Product Code:32903Composition:Hydrated aluminum silicate, pyrophyllitePhysical State:White to cream powder

	Specification	Test Method
*Fineness, retained on 200 mesh	1.0% maximum	T-957
*Brightness	78 minimum	T-900

GENERAL INFORMATION

Typical values not routinely measured or reported on the Certificate of Analysis.

Density at 25°C	2.80 Mg/m ³
Loss on Ignition	3.1%

*Certified Property

Uses - Inert filler and extender for NR and synthetic rubbers and latexes for reducing volume costs and where low moisture pick-up is required. The platy particle shape imparts "mud-cracking" resistance in coatings. Also used in crack fillers and joint cements.

PYRAX is a registered trademark of R.T. Vanderbilt Holding Company, Inc. and/or its respective wholly owned subsidiaries.

The information presented herein, while not guaranteed, was prepared by technical personnel and, to the best of our knowledge and belief, is true and accurate as of the date hereof. No warranty, representation or guarantee, express or implied, is made regarding accuracy, performance, stability, reliability or use. This information is not intended to be all –inclusive, because the manner and conditions of use, handling, storage and other factors may involve other or additional safety or performance considerations. The user is responsible for determining the suitability of any material for a specific purpose and for adopting such safety precautions as may be required. Vanderbilt Minerals, LLC does not warrant the results to be obtained in using any material, and disclaims all liability with respect to the use, handling or further processing of any such material. No suggestion for use is intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patent or to violate any federal, state or local law or regulation.