

## **Specification**

## VANLUBE® AZ Lubricant Additive

November 22, 2023

RTV Product Code: 50401

Composition: Zinc diamyldithiocarbamate in oil

Physical State: Amber liquid

<u>Specification</u> <u>Test Method</u>

\*Color, ASTM 5.0 maximum ASTM D-1500

\*Sulfur Content 11.0-13.5% EA-1

\*Zinc Content 6.0-6.5% T-365, AA-16

## **GENERAL INFORMATION**

Typical values not routinely measured or reported on the Certificate of Analysis.

Density at 15.6°C 1.02 Mg/m<sup>3</sup>

Viscosity at 100°C 9.8 cSt

Solubility - Soluble in petroleum fuels and lubricants. Insoluble in water.

\*Certified Property

Uses - Used in petroleum products as an oxidation inhibitor, a metal deactivator, an anti-wear agent and a bearing corrosion inhibitor.

The information presented herein, while not guaranteed, was prepared by technical personnel and, to the best of our knowledge and belief, is true and accurate as of the date hereof. No warranty, representation or guarantee, express or implied, is made regarding accuracy, performance, stability, reliability or use. This information is not intended to be all –inclusive, because the manner and conditions of use, handling, storage and other factors may involve other or additional safety or performance considerations. The user is responsible for determining the suitability of any material for a specific purpose and for adopting such safety precautions as may be required. Vanderbilt Chemicals, LLC does not warrant the results to be obtained in using any material, and disclaims all liability with respect to the use, handling or further processing of any such material. No suggestion for use is intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patent or to violate any federal, state or local law or regulation.