

Specification

VANLUBE® RI-A	4®
Lubricant Additive	

December 16, 2013

RTV Product Code:50722Composition:Dodecenylsuccinic acid reaction productPhysical State:Amber liquid

	Specification	Test Method
*Color, ASTM	3.0 maximum	ASTM D1500
*Total Acid Number	105 – 145 mg KOH/g	T-977

GENERAL INFORMATION

Typical values not routinely measured or reported on the Certificate of Analysis.

Density at 15.6°C	0.98 Mg/m3
Viscosity at 100°C	16 mm²/s

Solubility - Soluble in petroleum products.

*Certified Property

Uses – Oil soluble. Ashless rust inhibitor.

VANLUBE is a registered trademark of R.T. Vanderbilt Holding Company, Inc. and/or its respective wholly owned subsidiaries.

The information presented herein, while not guaranteed, was prepared by technical personnel and, to the best of our knowledge and belief, is true and accurate as of the date hereof. No warranty, representation or guarantee, express or implied, is made regarding accuracy, performance, stability, reliability or use. This information is not intended to be all –inclusive, because the manner and conditions of use, handling, storage and other factors may involve other or additional safety or performance considerations. The user is responsible for determining the suitability of any material for a optimic purpose and for adopting such safety precautions as may be required. Vanderbilt Chemicals, LLC does not warrant the results to be obtained in using any material, and disclaims all liability with respect to the use, handling of further processing of any such material. No suggestion for use is intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patent or to violate any federal, state or local law or regulation.