

# Vistalon™ 878P

## Ethylene Propylene Copolymer Rubber

Product Description	Key Features
Vistalon™ 878P EPDM rubber is a medium Mooney viscosity, medium ethylene content copolymer of ethylene and propylene with a narrow molecular weight distribution. This product is sold in pellet form.	Major applications include plastic modification such as the production of TPOs. Features excellent mixing and processing.

General		
Availability <sup>1</sup>	▪ Latin America	▪ North America
Form(s)	▪ Pellets	
Revision Date	▪ 10/05/2021	

Physical	Typical Value (English)	Typical Value (SI)	Test Based On
Mooney Viscosity <sup>2</sup> (ML 1+4, 257°F (125°C))	48 MU	48 MU	ASTM D1646 (mod)
Ethylene Content	61.0 wt%	61.0 wt%	ASTM D3900A

Legal Statement
For detailed Product Stewardship information, please contact Customer Service.

This product, including the product name, shall not be used or tested in any medical application without the prior written acknowledgement of ExxonMobil Chemical as to the intended use. For detailed Product Stewardship information, please contact Customer Service.

Notes
Typical properties: these are not to be construed as specifications.
<sup>1</sup> Product may not be available in one or more countries in the identified Availability regions. Please contact your Sales Representative for complete Country Availability.
<sup>2</sup> Radial cavity dies, polymer remassed at 145±10°C.

For additional technical, sales and order assistance: [www.exxonmobilchemical.com/ContactUs](http://www.exxonmobilchemical.com/ContactUs)

©2022 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Product Solutions" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Product Solutions Company, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.

[exxonmobilchemical.com](http://exxonmobilchemical.com)